

ICM 34/38



fiorentini



ICM 34/38

MODEL TECHNICAL SPECIFICATION		ICM 34 UE	ICM 38 UE	ICM 38 GAS
Scrubbing width	mm	850	950	950
Cleaning capacity up to	m ² /h	5100	5700	11400
Operating range	h	5,0	5,0	/
Solution tank capacity	l	190	190	190
Recovery tank capacity	l	180	180	150
Waste tank capacity	l	/	16,0	/
TECHNICAL DATES				
Mechanical drive (front/rear)		rear	rear	rear
Mechanical drive (drivingwheel/diff./hydrost.)		n. 2 gear motor	n. 2 gear motor	n. 2 hydraulic motor
Forward speed	km/h	6,0	6,0	12
Max. slope	%	12	12	13
Water lift	mm	1600	1600	
Brush pressure	kg	0/60	0/60	0/60
Noise level	dB	83	83	88
Turning radius	mm	2750	2750	2750
ELETTRIC DATES				
Power	v	36	36	36
Vacuum motor	w	2 x 850 w	2 x 850 w	600/3 stadi
Brush motor	w	2 x 750 w	3 x 750 w	OR 80 C.
Traction motor	w	2 x 550 w	2 x 550 w	EPMW 160
Voltage		290A	290A	/
ENGINE POWER				
Endothermic motor		/	/	GPL
DIMENSION & WEIGHT				
Length	mm	1800	1800	1700
Width	mm	1050	1000	1000
Height	mm	1460	1460	1500
Number of brushes and diameter	mm	n°2 Ø 410	n°3 Ø 330	n°3 Ø 330
Squeegee width	mm	1300	1300	1300
Weight of the machine [without batteries/ water/ operator]	kg	/	/	/
Weight of the batteries (approx)	kg	385	385	/



ING. O. FIORENTINI s.r.l.

“THE BEST IN FLOOR MACHINES”
 afiorentini@ingfiorentini.it sales@ingfiorentini.it
 www.ingfiorentini.it

FILIALI:
 20132 MILANO – Fax. 02-2592779
 Via Palmanova 211/a – Tel. 02-27207783 - 2564810
 00155 ROMA – Fax. 06-22754075
 Via Carlo Carrà 13 – Tel. 06-22754040-2275060

STABILIMENTO:
 50030 PIANCALDOLI (FI) – Fax. 055-817144
 Loc. Rombola - Tel. 055-8173610

Distributed by:

